

EUP150T-1H24V-0 (-)
Product Feature

- Single-channel constant voltage output, 6.3A Max.
- Support Leading edge (Triac) and Trailing edge (ELV) Dimmer.
- Dimming range from 40VAC to 240V AC.
- Dimming effect smooth, no flicker
- High efficiency: up to 89%.
- Over Power protection; Over voltage protection; Short circuit protection;
- Suitable for indoor LED lighting application


Application


Wall Washer



LED Strip Light



LED Tube




Underground Light



AR111 Venture Light

Technical Parameters

Model	EUP150T-1H24V-0	
Input	Efficiency	89%(Typical)
	Voltage	200VAC-240VAC
	Frequency	50/60Hz
	Power Factor	/
	Current	2A@230VAC
	Dimming voltage range	40-240VAC
	Inrush Current	45A@230VAC
Output	Current/Voltage/Power	6.3A/24VDC/151.2W
	Ripple Current	200mVp-p
	Channel	1
	Voltage Tolerance	±3%
	Turn On Delay Time	<1s, at 230Vac
Function	Dimming Mode	Triac ELV
	Dimming Range	1-100% Dimming to off
Protection	Over Power	Limit the output power to 110% - 150% of the rated power
	Short Circuit	Close the output, restart to recover since fault condition is removed for 10s
	Over voltage	Hiccup, recovers after fault condition is removed
Others	Working Temp.	-20°C~50°C
	Storage Temp.; Humidity	-40°C~85°C, 20-90%RH
	Tc	75°C
	Material	Metal
	IP Rating	IP20
	Lifetime	30,000h@tc:75°C
	Warranty Condition	3 years
	Switch Cycle	>15,000 times
	Packing Size	Net weight: 842g±5%/PCS; 20PCS/Carton; 18kg±5%/Carton; Carton Size: 367*292*289mm(L*W*H)
Dimension	260*78.3*45mm(L*W*H)	

Dimension(mm)


Wiring Diagram**Cautions**

- 1.The product shall be installed and serviced by a qualified person.
- 2.This product is non-waterproof. Please avoid the sun and rain. When installed outdoors please ensure it is mounted in a water proof enclosure.
- 3.Good heat dissipation will prolong the working life of the controller. Please ensure good ventilation.
- 4.Please check if the output voltage and current of any LED power supplies used comply with the requirement of the product.
- 5.Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- 6.For safety consideration, PVC or rubber cord of 0.75-1.5mm² is recommended for input and output terminal(s) . Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- 7.If a fault occurs please return the product to your supplier. Do not attempt to fix this product by yourself.

※ The contents of this manual are updated without prior notice. If the function of the product you are using is inconsistent with the instructions, the function of the product shall prevail.Please contact us if you have any questions.

EUP150T-1H24V-0 (-)

产品特点

- 单通道恒压输出，最大输出电流6.3A
- 支持前沿 (Triac) 和后沿(ELV)调光
- 调光电压范围 40VAC- 240VAC.
- 调光曲线平滑，无抖动
- 高效率达89%
- 过功率保护；过压保护；短路保护；
- 适用于室内LED灯具



应用



洗墙灯



LED灯带



LED硬灯条



地埋灯





AR斗胆灯

技术参数

型号	EUP150T-1H24V-0	
输入	效率	89%(典型)
	电压	200VAC-240VAC
	频率	50/60Hz
	功率因素	/
	电流	2A@230VAC
	调光电压范围	40-240VAC
	浪涌电流	45A@230VAC
输出	电流/电压/功率	6.3A/24VDC/151.2W
	波纹电流	200mVp-p
	通道	1
	电压精度	±3%
	启动延时	/
功能	调光方式	前沿 后沿可控硅
	调光范围	1-100% 变暗至关闭
保护	过功率	将输出功率限值在额定功率的110%-150%
	短路	锁死，去除故障 10s 后重新上电可恢复
	过压	打嗝，去除故障后自恢复
其它	工作温度	-20°C~50°C
	储存温度、湿度	-40°C~85°C, 20-90%RH
	tc	75°C
	材质	金属
	防水等级	IP20
	寿命	30,000小时@tc:75°C
	质保	3年
	开关周期	>15,000次
	包装重量	净重: 842g±5%/个; 20个/箱; 18kg±5%/箱; 外箱尺寸: 367*292*289mm(L*W*H)
尺寸	260*78.3*45(长*宽*高)	

产品尺寸



应用接线图



注意事项

1. 本产品请由具有专业资格的人员进行调试安装。
2. 本产品不能防水，需避免日晒雨淋，如安装在户外，请用防水箱。
3. 良好的散热条件会延长产品的使用寿命，请把产品安装在通风良好的环境。
4. 请检查使用的LED电源输出电压电流，是否符合产品要求。
5. 出于安全考虑，推荐输入和输出(信号端除外)用0.75-1.5mm²PVC或橡胶线缆，并确保接线牢固，以免电线过热或接触不良触发事故。扁平电源线不适用。
6. 通电调试前，应确保所有接线正确，以避免因接线错误而导致灯具损坏。
7. 如果发生故障，请勿私自维修；如有疑问，请联系供应商。

※ 本说明书内容如有更新，恕不另行通知。若您使用的产品功能与说明书不一致时，请以产品为准。如有疑问请与我们联系。